

Katy A. Holdredge

INTERNATIONAL ELECTROTECHNICAL COMMISSION **IEC Certification System for Explosive Atmospheres**

for rules and details of the IECEx Scheme visit www.iecex.com

Certificate No.: **IECEx ULD 21.0033X** Page 1 of 3 Certificate history:

Issue No: 0 Status: Current

2022-04-27 Date of Issue:

Applicant: Prosense Teknoloji San. Ltd. Sti. Cumhuriyet Mah, Mermer Sk. No:16

KARTAL - Istanbul 34876

Türkiye

Equipment: Gas Detector, Series PQ*

Optional accessory:

Type of Protection: Flameproof "db", Dust Ignition Protection by Enclosure "tb"

Marking: Ex db IIC T6 Gb

> Ex tb IIIC T85°C Db -40°C ≤ Ta ≤ +70°C

Approved for issue on behalf of the IECEx

Certification Body:

Position: Senior Staff Engineer

Signature:

(for printed version)

(for printed version)

- This certificate and schedule may only be reproduced in full.
 This certificate is not transferable and remains the property of the issuing body.
 The Status and authenticity of this certificate may be verified by visiting www.iecex.com or use of this QR Code.



Certificate issued by:

UL International DEMKO A/S Borupvang 5A DK-2750 Ballerup **Denmark**





Certificate No.: IECEx ULD 21.0033X Page 2 of 3

Date of issue: 2022-04-27 Issue No: 0

Manufacturer: Prosense Teknoloji San. Ltd. Sti.

Cumhuriyet Mah, Mermer Sk. No:16

KARTAL - Istanbul 34876

Türkiye

Manufacturing Prosense Teknoloji San. Ltd. Sti.

locations: Cumhuriyet Mah, Mermer Sk. No:16 KARTAL - Istanbul 34876

Türkiye

This certificate is issued as verification that a sample(s), representative of production, was assessed and tested and found to comply with the IEC Standard list below and that the manufacturer's quality system, relating to the Ex products covered by this certificate, was assessed and found to comply with the IECEx Quality system requirements. This certificate is granted subject to the conditions as set out in IECEx Scheme Rules, IECEx 02 and Operational Documents as amended

STANDARDS:

The equipment and any acceptable variations to it specified in the schedule of this certificate and the identified documents, was found to comply with the following standards

IEC 60079-0:2017 Explosive atmospheres - Part 0: Equipment - General requirements

Edition:7.0

IEC 60079-1:2014-06 Explosive atmospheres - Part 1: Equipment protection by flameproof enclosures "d"

Edition:7.0

IEC 60079-31:2013 Explosive atmospheres - Part 31: Equipment dust ignition protection by enclosure "t"

Edition:2

This Certificate **does not** indicate compliance with safety and performance requirements other than those expressly included in the Standards listed above.

TEST & ASSESSMENT REPORTS:

A sample(s) of the equipment listed has successfully met the examination and test requirements as recorded in:

Test Report:

DK/ULD/ExTR21.0035/00

Quality Assessment Report:

GB/EXV/QAR18.0006/03



Certificate No.: IECEx ULD 21.0033X Page 3 of 3

Date of issue: 2022-04-27 Issue No: 0

EQUIPMENT:

Equipment and systems covered by this Certificate are as follows:

Prosense PQ series Gas and Vapor Detection Equipment comprise an Aluminium or Stainless-steel enclosure provided with up to 3 no. threaded entries for field wiring and one for the threaded device containing the detector module. The threaded cover allows access to the wiring terminals and PCB's. The PQ Gas Detector is intended to indicate presence of flammable and toxic gases in air or oxygen by atmospheric aspiration only. PQN provides RS-485 output and includes relay connection for external annunciation or control; as well as these features, the PQD incorporates a sight glass allowing review of the integral display. Data log function may be provided, as well as battery cell back-up.

Please see Annex for additional information.

SPECIFIC CONDITIONS OF USE: YES as shown below:

- · Flamepaths must not be repaired.
- When the painted enclosure is intended for use in Group III applications, the end user must adhere to the manufacturer's instructions to minimise risk of electrostatic discharge.
- · PQ Series gas detectors must be installed only with sensor head pointing downwards.

Annex:

Annex to IECEx ULD 21.0033X Issue 0.pdf



Certificate No.: IECEx ULD 21.0033X

Issue No.: 0

Page 1 of 2

IECEx

TYPE DESIGNATION

Nomenclature:

Gas detector	Display	SIL	Gas type	Sensing head	Sensor type	Cable entry	Certification		
PQ = PQ	Series gas o	detector							
	D- = With	= With display							
	N- = With	N- = Without display							
		S- = SIL version electronics (SIL not part of this certification)							
		xx = two digits (Gas type not part of this certification).							
		1 = SH10							
		2 = SH20							
				3 = SH30					
			1 = Semiconductor						
			2 = Catalytic						
			3 = Infrared						
					4 = Electrochemical				
					5 = Pellistor				
			6 = PID						
					7 = MPS				
						T1 = 1/2" NP NPT	T, 1/2" NPT, 1/2" NPT, 3/4"		
						T2 = 3/4" NP NPT,	T, 3/4" NPT, 3/4" NPT, 3/4"		
						T3 = M20, M20, M20, 3/4" NPT			
						<u>, </u>	C1 = ATEX, UKEX and		

PARAMETERS RELATING TO THE SAFETY

Input: 12-24 Vdc, 4 W max. Signal / output: 4-20mA Relays: 30Vdc, 1.25 A max.



Certificate No.: IECEx ULD 21.0033X

Issue No.: 0

Page 2 of 2

MARKING

Marking has to be readable and indelible; it has to include the following indications:

ProsenseMermer S. 16 34876 TURKEY
PQ Series PQD-3135 T1 C1 SN:ZZZZZ Yr YYYY

Ex db IIC T6 Gb
Ex tb IIIC T85°C Db

Ex tb IIIC T85°C Db IECEx ULD 21.0033X UL 21 ATEX 2656X Gas: Methane Range:0-100 %LEL Vmax 24VDC Pmax 4W -40°C ≤ Ta ≤ +70°C



WARNING – DO NOT OPEN WHEN AN EXPLOSIVE ATMOSPHERE IS PRESENT SEE INSTRUCTIONS FOR SPECIAL CONDITIONS OF USE AND CABLE ENTRY DETAILS