

## SMART S-SS TX SINGLE SENSOR HEAD & SINGLE OUTPUT with DISPLAY



Designed to meet with the toughest industrial requirements, **SMART S-SS** line allows monitoring flammable, toxic and refrigerant gases in harsh environments. These detectors have been certified to SIL 2 Hardware SIL 3 Software capability.

**SMART S-SS** are ATEX certified for zone 1 as II2G Ex db IIC T5 Gb



S-SS 4A (copper free Al enclosure)



S-SS 2S (SS enclosure)

### Sensor heads to be selected among S4, S6, S8

#### 4A Transmitter Exd Aluminum enclosure, copper free, electronics and features

CODE	DESCRIPTION		
SSS4A 11	Electronic with1 output RS485+4-20mA, LCD display		
SSS4A 12	Electronic with1 output RS485+4-20mA, LED display		
SSS4A 13	Electronic with1 output RS485+4-20mA, LCD display, 3-relay card		
SSS4A 14	Electronic with1 output RS485+4-20mA, LED display, 3-relay card		
SSS4A 17	Electronic with1 output RS485+4-20mA, LCD display, 3-relay card, Modem Hart		
SSS4A 18	Electronic with1 output RS485+4-20mA, LED display, 3-relay card, Modem Hart		

#### 2S Transmitter Stainless steel enclosure, electronics and features

CODE	DESCRIPTION		
SSS2S 11	Electronic with1 output RS485+4-20mA, LCD display		
SSS2S 12	Electronic with1 output RS485+4-20mA, LED display		
SSS2S 13	Electronic with1 output RS485+4-20mA, LCD display, 3-relay card		
SSS2S 14	Electronic with1 output RS485+4-20mA, LED display, 3-relay card		
SSS2S 17	Electronic with1 output RS485+4-20mA, LCD display, 3-relay card, Modem Hart		
SSS2S 18	Electronic with1 output RS485+4-20mA, LED display, 3-relay card, Modem Hart		

Examples of possible solutions:



SSS4A12-S4003ME



SSS4A12-S6002ME



SSS2S12-S4003ME